

LPG Dispenser – Double Nozzle

Double-nozzle LPG dispenser for retail gas outlets



NMDPRA-compliant



Calibrated before delivery



Assembled & tested in Nigeria



Spare parts always available

Built for accurate, safe retail LPG dispensing. It measures every kilogram precisely at $\pm 0.3\%$, protecting both your margin and your customers' trust, with an air separator for clean, reliable dispensing. It serves two customers at once, each nozzle with its own meter and air separator, so busy outlets stay fast without losing precision. Very low noise in operation, 7-year memory with battery backup, calibrated before delivery and installed by MEGA-TEC's certified technicians.

Gas LPG

TECHNICAL PARAMETERS		OPERATING CONDITIONS	
Nozzle	2	Meter accuracy	$\pm 0.3\%$
Hose	2	Working pressure	0.3 MPA
Display	4	Suction distance	Min 30m · Max 35m
Product suction	2	Ambient temperature	-20°C to +80°C
Standard meter	2	Relative humidity	45% – 85%
Air separator	2	Noise	Very low, under 72 dB

SPECIFICATIONS

Nozzle	O.P.W 1" · blue or red guard
Hose	4m flexible, wire reinforced, oil resistant, 1" dia.
Hose hanger	Attached to the frame, retractable
Control valve	In-line valves
Meter	4-piston positive displacement · aluminium alloy frame
Pump unit	Self-priming gear pump with oil separator and air eliminator
Electric motor	Single phase, flame proof, 220V 50Hz 1kW
Totalizer	Electronic / mechanical, visible from outside
Frame	White (other colours available on request)
Money calculating range	000-00009999.99 MU
Register range	000-00009999.99 / L
Unit price setting range	000-0009999.99 / L
Totalizer range	0.009,999,999.99 L
Memory storage & backup	10-minute backup · over 7 years memory storage
Security	Electronic
Manual	Maintenance and installation included

Ready to order, or need advice? Message or call our technical team on [+234 904 315 4982](tel:+2349043154982). We reply within 24 hours. No pressure to buy, just honest, straightforward advice from our team.