

## MT PLUS – Single Nozzle (BB)

Single-nozzle fuel dispenser · Bennett meter, Bennett unit



NMDPRA-compliant



Calibrated before delivery



Assembled & tested in Nigeria



Spare parts always available

A dependable single-nozzle dispenser built on a full Bennett meter and Bennett unit. Calibrated to  $\pm 0.3\%$  before delivery, assembled and tested in Nigeria on openly available components, and serviceable by any engineer nationwide, so spare parts are never a problem.

### Compatible fuels

PMS, AGO or DPK

| TECHNICAL PARAMETERS |   | OPERATING CONDITIONS |                       |
|----------------------|---|----------------------|-----------------------|
| Nozzle               | 1 | Flow rate            | 5 to 50 L/min         |
| Hose                 | 1 | Meter accuracy       | $\pm 0.3\%$           |
| Display              | 2 | Working pressure     | 0.3 MPA               |
| Product suction      | 1 | Suction distance     | Min 30m · Max 35m     |
| Bennett meter        | 1 | Ambient temperature  | -20°C to +80°C        |
| Bennett unit         | 1 | Relative humidity    | 45% – 85%             |
| Electric motor       | 1 | Noise                | Very low, under 72 dB |

### SPECIFICATIONS

|                          |                                                              |
|--------------------------|--------------------------------------------------------------|
| Nozzle                   | O.P.W 1" · blue or red guard                                 |
| Hose                     | 4m flexible, wire reinforced, oil resistant, 1" dia.         |
| Hose hanger              | Attached to the frame, retractable                           |
| Control valve            | In-line valves                                               |
| Meter                    | 4-piston positive displacement · aluminium alloy frame       |
| Pump unit                | Self-priming gear pump with oil separator and air eliminator |
| Electric motor           | Single phase, flame proof, 220V 50Hz 1kW                     |
| Totalizer                | Electronic / mechanical, visible from outside                |
| Frame                    | White (other colours available on request)                   |
| Money calculating range  | 000-00009999.99 MU                                           |
| Register range           | 000-00009999.99 / L                                          |
| Unit price setting range | 000-0009999.99 / L                                           |
| Totalizer range          | 0.009,999,999.99 L                                           |
| Memory storage & backup  | 10-minute backup · over 7 years memory storage               |
| Security                 | Electronic                                                   |
| Manual                   | Maintenance and installation included                        |

Ready to order, or need advice? Message or call our technical team on **+234 904 315 4982**. We reply within 24 hours. No pressure to buy, just honest, straightforward advice from our team.